

Humidity Meter & Dew Point Meter



Model: HT-1292 (Humidity Meter)
HT-1292D (Dew Point Meter)

Applications

Widely used in workshops, offices, libraries, computer stations, laboratories and warehouses.

* HT-1292 is able to measure Humidity, Temperature, Wet Bulb Temperature.

* HT-1292D is able to measure Humidity, Temperature, Wet Bulb Temperature, Dew Point Temperature



Specifications

Model	HT-1292	HT-1292D
Display	Backlit LCD	
Range	Humidity	10~95%RH
	Temp.	-10~60°C(14~140°F)
	Wet Bulb Temp.	-10~60°C(14~140°F)
	Dew Point Temp.	— -40~40°C
Resolution	Humidity	0.1%RH
	Temp.	0.1°C / 0.1°F
	Wet Bulb Temp.	0.1°C / 0.1°F
	Dew Point Temp.	— 0.1°C
Accuracy	Humidity	2.5%±1%RH
	Temp.	±0.5°C
	Wet Bulb Temp.	±0.5°C
	Dew Point Temp.	— ±1°C
Sensor	Humidity	Capacitor
Type	Temp.	Resistor
Sampling Time	0.4 Seconds	
Memory	Last Value, Max. Value, Min Value	
Time Base	Quartz Crystal	
Power Supply	4x1.5V AAA (UM-4) Battery	
Dimensions	171x72x34mm (6.7x2.8x1.3inch)	
Weight	145g/0.32lb(Not Including Batteries)	
Standard Accessories	Main Unit	
	Carrying Case	
	Operation Manual	

Features

- * Used the exclusive MICRO-COMPUTER LSI circuit and crystal time base to offer the high accuracy measurement & fast measuring time.
- * Digital display gives exact reading with no guessing.
- * Wide measuring range & high resolution.
- * The Last Values / Max. Values / Min. Values of both Humidity and Temperature will be automatically stored in memory and can be displayed by turn.
- * The use of durable, long-lasting components, including a strong, light weight ABS-plastic housing assures maintenance free performance for many years. The housing has been carefully shaped to fit in either hand.