

TES-1364 / TES-1365 HUMIDITY TEMPERATURE METER



PRODUCT FEATURES

- Detachable sensing probe.
- Dual LCD display with Bargraph indication.
- Dew Point Reading.
- Wet bulb Reading.
- MAX/MIN with Time Stamp.
- Data Hold & Relative function.
- Datalogging capacity 15,000 dual reading. (%RH & Temp). (TES-1365)
- USB interface & windows software. (TES-1365)
- Automatic Timer Recording for Datalogger. (TES-1365)

Measuring Range	Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 10%RH ~ 95%RH
Resolution	0.1°C/0.1°F/0.1%RH
Accuracy	Temperature : ±0.5°C, ±0.9°F Humidity : ±3%RH (at 25°C, 30 ~ 95% RH). ±5%RH (at 25°C, 10 ~ 30% RH).
Datalogging	Manual recording : 99 data sets. (Direct reading from LCD display.) Continue recorder : 15,000 data sets. (Automatic timer recording, USB interface/software.) (TES-1365)

Input Protection	60V DC or 24 Vrms AC maximum input voltage on any Combination of input Connector.
Sampling Rate	2 times/sec
Operating Conditions	0°C ~ 60°C (32°F ~ 140°F) & 10 ~ 80% R. H.
Power Source	6 pcs size "AAA" Batteries.
Battery Life	Approx. 200 hours.
Size & Weight	150(L)×72(W)×35(H)mm & Approx. 235g
Accessories	1. Instruction manual, Battery. 2. RS-232 to USB optical cable & Software. (TES-1365) 3. AC adaptor (Optional).

SIAFA
www.siafa.com.ar